

Output Function	NPN, NO	XT06-D310-F	XT06-D311-F	XT06-D313-F	XT06-D364-F
	PNP, NO	XT06-D410-F	XT06-D411-F	XT06-D413-F	XT06-D464-F
	NPN, NC	XT06-D510-F	XT06-D511-F	XT06-D513-F	XT06-D564-F
	PNP, NC	XT06-D610-F	XT06-D611-F	XT06-D613-F	XT06-D664-F
<p>6.5 mm Diameter Extended Operating Distance Unthreaded body with cable or integral connector to simplify installation. DC 3 wire.</p>					
<p>Operating Distance</p>		2 mm		3 mm	
<p>Power Supply</p>		6 - 30 VDC			
<p>Power Drain</p>		< 12 mA			
<p>Voltage Drop (on state)</p>		< 1.8 V			
<p>Switching Current (max)</p>		200 mA max.			
<p>Short Circuit Protection</p>		Yes			
<p>Operating Frequency</p>		2 kHz max.			
<p>Repeatability</p>		≤ 3%			
<p>Case</p>		Stainless Steel			
<p>Flush Mounting</p>		Yes		No	
<p>Protection Degree</p>		IP 67			
<p>Operating Temperature</p>		-25°C to +70°C			
<p>Output Connection</p>		Cable: PVC, 22 AWG, 2 m long		Connector - RP-522	

CE RoHS

Output Function	NPN, NO	T08-D310-F	T08-D318-F	T08-D313-F
	PNP, NO	T08-D410-F	T08-D418-F	T08-D413-F
	NPN, NC	T08-D510-F	T08-D518-F	T08-D513-F
	PNP, NC	T08-D610-F	T08-D618-F	T08-D613-F
<p>8 mm Diameter Threaded body with cable or integral connector to simplify installation. DC 3 wire.</p>				
<p>Operating Distance</p>		2 mm		
<p>Power Supply</p>		10 - 30 VDC		
<p>Power Drain</p>		< 12mA		
<p>Voltage Drop (on state)</p>		< 1.8 V		
<p>Switching Current (max)</p>		200 mA max.		
<p>Short Circuit Protection</p>		Yes		
<p>Operating Frequency</p>		2 kHz max.		
<p>Repeatability</p>		≤ 3%		
<p>Case</p>		Stainless Steel		
<p>Flush Mounting</p>		Yes		
<p>Protection Degree</p>		IP 67		
<p>Operating Temperature</p>		-25°C to +70°C		
<p>Output Connection</p>		Cable: PVC, 22 AWG, 2 m long	Connector - RP-526	Connector - RP-522

CE RoHS